

OSHA's Final Rule to Update, Align, and Provide Greater Flexibility in its General Industry Walking-Working Surfaces and Fall Protection Standards

Background

Falls from heights and on the same level (a working surface) are among the leading causes of serious work-related injuries and deaths. OSHA estimates that, on average, approximately 202,066 serious (lost-workday) injuries and 345 fatalities occur annually among workers directly affected by the final standard. OSHA's final rule on Walking-Working Surfaces and Personal Fall Protection Systems better protects workers in general industry from these hazards by updating and clarifying standards and adding training and inspection requirements. The rule affects a wide range of workers, from window washers to chimney sweeps. It does not change construction or agricultural standards.

The rule incorporates advances in technology, industry best practices, and national consensus standards to provide effective and cost-efficient worker protection. Specifically, the rule updates general industry standards addressing slip, trip, and fall hazards (subpart D), and adds requirements for personal fall protection systems (subpart I).

OSHA estimates this rule will prevent 29 fatalities and 5,842 lost-workday injuries every year.

The rule benefits employers by providing greater flexibility in choosing a fall protection system. For example, it eliminates the existing mandate to use guardrails as a primary fall protection method and allows employers to choose from accepted fall protection systems they believe will work best in a particular situation — an approach that has been successful in the construction industry since 1994. In addition, employers will be able to use non-conventional fall protection in certain situations, such as designated areas on low-slope roofs.

As much as possible, OSHA aligned fall protection requirements for general industry with those for construction, easing compliance for employers who perform both types of activities.

For example, the final rule replaces the outdated general industry scaffold standards with a requirement that employers comply with OSHA's construction scaffold standards.

The rule phases out a 1993 exception for the outdoor advertising industry that allows "qualified climbers" to forego fall protection. At least three workers have fallen from fixed ladders under this exception. One of them died. The final rule phases in the fixed ladder fall protection requirements for employers in outdoor advertising.

Fall Protection Options

The rule requires employers to protect workers from fall hazards along unprotected sides or edges that are at least 4 feet above a lower level. It also sets requirements for fall protection in specific situations, such as hoist areas, runways, areas above dangerous equipment, wall openings, repair pits, stairways, scaffolds, and slaughtering platforms. And it establishes requirements for the performance, inspection, use, and maintenance of personal fall protection systems.

OSHA defines fall protection as "any equipment, device, or system that prevents a worker from falling from an elevation or mitigates the effect of such a fall." Under the final rule, employers may choose from the following fall protection options:

- **Guardrail System** – A barrier erected along an unprotected or exposed side, edge, or other area of a walking-working surface to prevent workers from falling to a lower level.
- **Safety Net System** – A horizontal or semi-horizontal, cantilever-style barrier that uses a netting system to stop falling workers before they make contact with a lower level or obstruction.
- **Personal Fall Arrest System** – A system that

arrests/stops a fall before the worker contacts a lower level. Consists of a body harness, anchorage, and connector, and may include a lanyard, deceleration device, lifeline, or a suitable combination. Like OSHA's construction standards, the final rule prohibits the use of body belts as part of a personal fall arrest system.

- **Positioning System** – A system of equipment and connectors that, when used with a body harness or body belt, allows a worker to be supported on an elevated vertical surface, such as a wall or window sill, and work with both hands free.
- **Travel Restraint System** – A combination of an anchorage, anchorage connector, lanyard (or other means of connection), and body support to eliminate the possibility of a worker going over the unprotected edge or side of a walking-working surface.
- **Ladder Safety System** – A system attached to a fixed ladder designed to eliminate or reduce the possibility of a worker falling off the ladder. A ladder safety system usually consists of a carrier, safety sleeve, lanyard, connectors, and body harness. Cages and wells are not considered ladder safety systems.

Rope Descent Systems

The rule codifies a 1991 OSHA memorandum that permits employers to use Rope Descent Systems (RDS), which consist of a roof anchorage, support rope, descent device, carabiners or shackles, and a chair or seatboard. These systems are widely used throughout the country to perform elevated work, such as window washing.

The rule adds a 300-foot height limit for the use of RDS. It also requires building owners to affirm in writing that permanent building anchorages used for RDS have been tested, certified, and maintained as capable of supporting 5,000 pounds for each worker attached. This mirrors the requirement in OSHA's Powered Platforms standard.

Ladder Safety Requirements

Falls from ladders account for 20 percent of all fatal and lost work-day injuries in general industry. The new rule includes requirements to protect workers from falling off fixed and portable ladders

as well as mobile ladder stands and platforms. (The ladder requirements do not apply to ladders used in emergency operations or ladders that are an integral part of or designed into a machine or piece of equipment).

In general, ladders must be capable of supporting their maximum intended load, while mobile ladder stands and platforms must be capable of supporting four times their maximum intended load. Each ladder must be inspected before initial use in a work shift to identify defects that could cause injury.

Fixed Ladders – Fixed ladders are permanently attached to a structure, building, or equipment. These include individual-rung ladders, but not ship stairs, step bolts, or manhole steps. The new rule phases in a requirement for employers to have ladder safety or personal fall arrest systems for fixed ladders that extend more than 24 feet, and phases out the use of cages or wells for fall protection under the following timeline: Starting in two years, all new fixed ladders and replacement ladder/ladder sections must have a ladder safety or personal fall protection system. For existing ladders, within two years, employers must install a cage, well, ladder safety system, or personal fall arrest system on fixed ladders that do not have any fall protection. Within 20 years, all ladders extending more than 24 feet must have a ladder safety or personal fall arrest system.

Portable Ladders – Portable ladders usually consist of side rails joined at intervals by steps, rungs, or cleats. They can be self-supporting or lean against a supporting structure. The final rule will be easier for employers and workers to understand and follow because it uses flexible performance-based language instead of detailed specification and design requirements. Under the revisions, employers must ensure that: rungs and steps are slip resistant; portable ladders used on slippery surfaces are secured and stabilized; portable ladders are not moved, shifted, or extended while a worker is on them; top steps and caps of stepladders are not used as steps; ladders are not fastened together to provide added length unless designed for such use; and ladders are not placed on boxes, barrels, or other unstable bases to obtain added height.

Training Requirements

The rule adds a requirement that employers ensure workers who use personal fall protection and work in other specified high hazard situations are trained, and retrained as necessary, about fall and equipment hazards, including fall protection systems. A qualified person must train these workers to correctly: identify and minimize fall hazards; use personal fall protection systems and rope descent systems; and maintain, inspect, and store equipment or systems used for fall protection.

When there is a change in workplace operations or equipment, or the employer believes that a worker would benefit from additional training based on a lack of knowledge or skill, then the worker must be retrained. The training must be provided in a language and vocabulary that workers understand.

Timeline

Most of the rule will become effective 60 days after it is published in the *Federal Register*, but some provisions have delayed effective dates, including:

- Ensuring exposed workers are trained on fall hazards (6 months),
- Ensuring workers who use equipment covered by the final rule are trained (6 months),
- Inspecting and certifying permanent anchorages for rope descent systems (1 year),

- Installing personal fall arrest or ladder safety systems on new fixed ladders over 24 feet and on replacement ladders/ladder sections, including fixed ladders on outdoor advertising structures (2 years),
- Ensuring existing fixed ladders over 24 feet, including those on outdoor advertising structures, are equipped with a cage, well, personal fall arrest system, or ladder safety system (2 years), and
- Replacing cages and wells (used as fall protection) with ladder safety or personal fall arrest systems on all fixed ladders over 24 feet (20 years).

Additional information

Additional information on OSHA's rule on walking-working surfaces and personal fall protection systems can be found at www.osha.gov/walking-working-surfaces. OSHA can provide extensive help through a variety of programs, including technical assistance about effective safety and health programs, workplace consultations, and training and education.

For more information on other safety-related issues impacting workers, to report an emergency, fatality, inpatient hospitalization, or to file a confidential complaint, contact your nearest OSHA office, visit www.osha.gov, or call OSHA at 1-800-321-OSHA (6742), TTY 1-877-889-5627.

This is one in a series of informational fact sheets highlighting OSHA programs, policies or standards. It does not impose any new compliance requirements. For a comprehensive list of compliance requirements of OSHA standards or regulations, refer to Title 29 of the Code of Federal Regulations. This information will be made available to sensory-impaired individuals upon request. The voice phone is (202) 693-1999; teletypewriter (TTY) number: (877) 889-5627.

For assistance, contact us. We can help. It's confidential.



**Occupational
Safety and Health
Administration**

www.osha.gov (800) 321-OSHA (6742)



U.S. Department of Labor